



STAND ALONE CARD READER ACCESS CONTROL



• RESIDENTIAL • COMMERCIAL



1520 Card Reader and Controller Only

- Single door / gate controllers
- Stores up to 1000 device codes
- 2 year limited factory warranty

Model 1520

- Full feature access controller
- Transaction/history buffer stores up to 3,656 events, anti-pass back, time zones, serial output for printer
- Built-in keypad for easy programming
- Controller only version allows you to add almost any 26-bit wiegand device (card reader, keypad, etc.)



1524 Card Reader, Remote, and Add/Delete Cards

Model 1524

- Available with the DK Prox reader only
- Programmed with hand held remote or with programming cards



keytags & proxis
designed to fit on a keyring



1524 basic
with or without housing





weigand controller
add your own device, whether keypads, card reader, or RF remote





simple wiring
easily connects to most electric strikes and magnetic locking devices as well as input from wiegand controllers

STAND ALONE ACCESS CONTROL CARD READERS



1520 Card Reader and Controller



1524 Card Readers

1520/1524 Card Reader

5.25" W x 6.25" H x 4.385" D (133mm W x 159mm H x 111mm D)

1520 Controller Only

5.25" W x 7.13" H x 4.75" D
(133mm W x 181mm H x 121mm D)

1524 Card Reader Only

1.75" W x 4.88" H x 1.0" D (44.5mm W x 124mm H x 25.4mm D)

1520	TYPE	MAX CODES	PROG FAC CODES*	TIME ZONES	HOLD OPEN CAPABILITY	OUTPUT	MAX ACCESS PTS	POWER	READ RANGE
Card Reader	Prox Card Reader	1000	10	4	Yes	1 Relay	1	16VAC or 12-24VDC	2-4 inches
Controller	Access Controller	1000	10	4	Yes	1 Relay	1	16VAC or 12-24VDC	-
1524	Prox Card Reader	1000	-	-	-	1 Relay	1	16VAC or 12-24VDC	2-4 inches

* Programmable Facility Codes

Technical Features

1524

Designed for single door or gate stand-alone applications
1000 card code memory

Programming via add/delete programming cards or with a hand-held remote device

Add/delete individual cards or blocks of cards

Available as a card reader only, or mounted on a lighted enclosure for outdoor use

Uses DK Prox card reader only

1520

Designed for single door or gate stand-alone applications
1000 card code memory

Programming via the built-in programming keypad

Available with DK Prox, AWID, HID readers, or can be ordered as a controller only (add your own 26-bit wiegand device)

Lighted enclosure for outdoor use

Transaction buffer stores last 3656 events

Built-in clock calendar

Four time zones and hold open time zones

Programmable facility codes

Anti-pass back

Print menu and real time print mode (printer not included)

Clock and transaction buffer will maintain data for up to three days in the event of a power failure

Miscellaneous

Output is a form C dry contact relay rated at 30 Volt, 1 Amp

16 VAC, 20 VA power transformer provided

Operating temperature -31° to 150° F (-35° to 65° C)

Shipping weight approximately 8 Lbs. (3.6 kg)

Card readers are ETL Listed



Access Control Solutions since 1948

Distributed by:



Power Door Products

(914) 698-5083

www.PowerDoorProducts.com